

Sea-Legs Twin Tube (for two-tube pontoon boats)

Two heavy duty hydraulically operated lift modules provide up to 5800 pounds of lift capacity.

Constructed of extruded aluminum alloy tubing and angled to provide strength and corrosion resistance.

Two large 18-inch x 48-inch pads support the pontoon on lake bottom.

Four hydraulic cylinders with steel alloy piston rods supply lifting power.



Sea-Legs attach permanently to your boat so you can take your lift with you wherever you go!



Lift height approximately 6 feet, measured from bottom of boat deck to lake bottom.

In retracted position, legs tuck neatly within 5 inches of pontoon deck; works with any pontoon trailer, no drag while in water.

Total weight added to boat approximately 340 pounds, evenly distributed.

No drifting, no anchors, no banging against the dock.

Two year limited warranty.

Single 1-hp pump tucked neatly under a seat activates the hydraulic cylinders.

Pump features an automatic shut-off alarm system to signal that the legs are fully retracted.

Sea-Legs are operated by either remote control or directly, via toggle switches located near the pump.

Sea-Legs Triple Tube (for three-tube pontoon boats)

Four heavy duty hydraulically operated lift modules provide up to 7500 pounds of lift capacity.

Four large 31" X 10" pads provide maximum support on any lake bottom.

Four hydraulic cylinders with steel alloy piston rods supply lifting power.

Single 1.5 horse power pump tucked neatly under a seat controls the hydraulic cylinders.

Lift height approximately 6 feet, measured from bottom of boat deck to lake bottom.



Sea-Legs attach permanently to your boat so you can take your lift with you wherever you go!



Total weight added to the pontoon approximately 540 pounds, evenly distributed.

Triple tube Sea-Legs are designed to always have two modules running at all times.

- Works with most triple tube pontoons. Sea-Legs requires 13 inches of clearance between the center tube and the outside tube.
- Sea-Legs is not designed to work with IO's
- The performance sheathing must be removed for installation.

Sea-Legs triple is operated by remote control allowing you total control of your lift.