

Trailmaster Channel Models

Channel construction offers rugged durability. There are no hidden areas to rust. All exposed surfaces are fully painted to prevent corrosion. Electrical wiring, lighting and brake lines are readily accessible for maintenance. The pivoting head bunk support system allows for hull conforming adjustability.



Trailmaster Channel Standard Single Axle

Trailmaster Model	Boat Length	Capacity	GVWR	Tires
SC1611	16	1100	1500	480X12B
SC1612	16	1250	1600	530X12B
SC1616	16	1600	2000	175/80D13C
SC1724	17	2400	2960	185/80D13C
SC1824	18	2400	2995	205/75D14C
SC1830BR	18	3000	3700	215/75D14C
SC2030BR	20	3000	3700	215/75D14C
SC2040BR	20	4000	5000	225/75D15D
SC2330BR	23	3000	3700	215/75D14C
SC2340BR	23	4000	5000	225/75D15D

Trailmaster Model	Boat Length	Capacity	GVWR	Tires
PC1724	17	2400	2960	185/80R13C
PC1824	18	2400	2995	205/75R14C
PC1830BR	18	3000	3700	215/75R14C
PC2030BR	20	3000	3700	215/75R14C
PC2040BR	20	4000	5000	225/75R15D
PC2330BR	23	3000	3700	215/75R14C
PC2340BR	23	4000	5000	225/75R15D



Trailmaster Channel Premium Tandem Axle

Trailmaster Model	Boat Length	Capacity	GVWR	Tires
T2050BBR	20	5000	6000	205/75R14C
T2050BR	20	5000	6000	205/75R14C
T2255BBR	22	5500	6500	205/75R14C
T2255BR	22	5500	6500	205/75R14C
T2258BBR	22	5800	7000	215/75R14C
T2258BR	22	5800	7000	215/75R14C
T2455BBR	24	5500	7000	205/75R14C
T2458BBR	24	5800	7400	215/75R14C
T2468BBR	24	6800	8300	225/75R15C
T2658BBR	26	5800	7400	215/75R14C
T2770BBR	27	7000	8500	225/75R15C
T28100BBR	28	10000	12000	235/85/R16D
T2880BBR	28	8000	10000	225/75R15D

TRI34105BBBR	34	10500	12900	225/75R15C
TRI38120BBBR	38	12000	15000	225/75R15D
TRI36150BBBR	36	15000	18000	235/85R16D
TRI42147BBBR	42	14700	18000	235/85R16D

Note: Some photos may show optional equipment.